



## SUBSTITUTING SODIUM BICARBONATE WITH SORBACAL® SP DRY INJECTION FOR SO<sub>2</sub> REMOVAL

### THE CHALLENGE

A municipal waste treatment plant had three independent, fluidized-bed waste incinerator lines, each with a flow of three metric tons/hour. To conform to new regulations for acid gas emissions (European Directive 2000/76/EC) the lines had been fitted with bi-reactive dry injection FGT units and fabric filters.

The dry injection units could operate with either calcium- or sodium-based sorbents. Sodium bicarbonate had always been used.

The site operators wanted to reduce acid gas emission levels further: to significantly below regulatory limits, particularly for SO<sub>2</sub>. The target values were 10 mg HCl/Nm<sup>3</sup> and 20 mg SO<sub>2</sub>/Nm<sup>3</sup>. These low values are desirable for plants equipped with post-filtration, low-temperature catalytic treatment of NO<sub>x</sub>.

To address the emission reduction goal, Lhoist proposed a demonstration of the technical and economic effectiveness of its Sorbacal® SP calcium-based sorbent. The plant operators scheduled a three-week trial period on two lines, with the third continuing to use sodium bicarbonate as a reference. The very brief notice – only two months – and the short trial made the exercise a real challenge.

### THE LHOIST SOLUTION

We provided a Sorbacal® Injecto-Matic Simplex DT unit fitted with a 50 m<sup>3</sup> silo. A dual injection head delivered sorbent to the two lines simultaneously. Simple, robust and relatively inexpensive, the unit was installed and working in less than a day.

Using Sorbacal® SP both lines operated below the levels of 10 mg HCl/Nm<sup>3</sup> and 15 mg SO<sub>2</sub>/Nm<sup>3</sup> – well within regulatory limits – and without requiring larger quantities of sorbent.

#### Sorbent performance during the three-week trial

	Sorbacal® SP	Sodium bicarbonate
Sorbent rate	11.3 kg/t OM Without fine-tuning	12 - 13 kg/t OM Nominal value
Gas rate at 11% O <sub>2</sub> [Nm <sup>3</sup> /h]	20,500	19,800
O <sub>2</sub> [%]	9.8 - 11	9.7 - 10.5
H <sub>2</sub> O [%]	12.8 - 14.5	15.5 - 17
HCl mg/Nm <sup>3</sup> at 11% O <sub>2</sub>	4 - 9	8 - 10
SO <sub>2</sub> mg/Nm <sup>3</sup> at 11% O <sub>2</sub>	1 - 8	8 - 12



## MUNICIPAL WASTE TREATMENT PLANT

### THE BENEFITS

The trial confirmed that the Lhoist package comprising a Sorbacal® Injecto-Matic and Sorbacal® SP met the operators' stringent emission targets. The unit's dual injection head was shown to efficiently deliver Sorbacal® to the two lines.

Despite the lack of time for fine-tuning during the trial, the results pointed to significant operating cost savings once conditions could be optimized. Additionally, the fast start-up demonstrated the package's convenience and suitability for the municipal incineration sector.



#### OUR EXPERTS CLOSE TO YOU

Find the best solution for your business by contacting one of our experts in your country or region via the contact page on [www.sorbacal.com](http://www.sorbacal.com).



[www.lhoist.com](http://www.lhoist.com)